

Microsemi MHM 2010™

Active Hydrogen Maser

MHM 2010 Front Panel



MHM 2010 Back Panel



Features

- Patented magnetic quadrupole for superior atomic beam focusing
- Low hydrogen usage for extended maintenance-free operation
- Demonstrated life of over 20 years
- Unique stand-alone auto-tuning feature provides exceptional long-term stability performance
- Proprietary Teflon™ coating technique, eliminating any re-coating requirement and extending maintenance-free life
- CE-compliant
- A low phase noise option for superior short-term stability in an active hydrogen maser
- Standard two year warranty

Applications

- Scientific frequency reference source
- National timekeeping service
- Radio astronomy: VLBI, VLBA
- Deep space tracking and navigation
- GNSS/GPS satellite monitoring

The MHM 2010 is the world's most widely installed active hydrogen maser for applications that require extreme frequency stability, low phase noise, and long service life. It is the only commercially available active hydrogen maser manufactured in the USA with a stand-alone cavity switching auto-tuning technique.

Hydrogen masers operate on the principle that hydrogen atoms, in the proper environment, emit radiation of a precise frequency (1420 MHz) and spectral line width (21 cm). Phase locking this extremely small power and high-purity signal to a very high-performance quartz oscillator, provides the user with incredible long-term stability, as well as excellent phase noise.

Active masers are typically four times more stable than passive hydrogen masers and 100 times more stable than high performance cesium up to 7 days of operation. Active maser advantages in metrology include low clock noise (eliminating the necessity for reference clock noise corrections) and a 10,000 times shorter interval to reach a specified frequency stability compared to high-performance cesium.

Each MHM 2010 is manufactured to meet quality standards, and carefully checked at each stage to ensure a top-quality product. Once built, the units are subjected to extensive performance testing, verifying all aspects of operation. All maser product design, manufacturing, and testing is conducted at a Microsemi facility dedicated to these operations.

Auto-Tuning

The MHM 2010 incorporates an automatic frequency control system to maintain the cavity at a constant frequency relative to the hydrogen emission line. This technique enables the MHM 2010 to deliver long-term stability that is only attributed to the most stable cesium atomic standards.

Environmental Sensitivity

The MHM 2010 is designed for low sensitivity to temperature, magnetic field, and power supply changes.

Outputs

The MHM 2010 provides multiple 5, 10, and 100 MHz outputs and 1PPS. Multiple configurations can be ordered to optimize the varied applications.

Microsemi MHM 2010™

Active Hydrogen Maser

Low Phase Noise Output Option

The MHM 2010 can be factory configured with low phase noise outputs that enable higher resolution measurements in VLBI applications and provide improved reference signals for maser timing systems. Users no longer have to face a trade-off between long-term and short-term stability.

Low Lifetime Cost of Ownership and Maintenance-Free Operation

Lifetime cost of ownership for active masers is a critical consideration. The MHM 2010 is designed for long life and low maintenance. The hydrogen supply is adequate for over 20 years of operation. An efficient hydrogen state selector minimizes the load on the ion pumps (<0.01 mole per year), and the pumps themselves are designed for over 20 years of life at nominal hydrogen flux. The Teflon bulb coating virtually eliminates any re-coating requirement and has a demonstrated life of over 20 years. Should it be required, the MHM 2010 is designed for on-site module replacement.

Specifications

Stability

Time	Allan Deviation (Measured in 0.5 Hz Bandwidth)	
	Standard	Low Phase Noise Option
1 s	1.5×10^{-13}	8.0×10^{-14}
10 s	2.0×10^{-14}	1.5×10^{-14}
100 s	5.0×10^{-15}	4.0×10^{-15}
1,000 s	2.0×10^{-15}	2.0×10^{-15}
10,000 s	1.5×10^{-15}	1.5×10^{-15}

- Floor* $<1.2 \times 10^{-15}$ typical (standard)
 $<1.0 \times 10^{-15}$ typical (low phase noise option)
- Long term** Typical spec ranges between 2×10^{-15} per day and 2×10^{-16} per day, depending on several factors in the operating environment
- Auto-tuning No external reference required

* Typically achieved after extended period of unperturbed, continuous operation. Temperature variation: ± 0.25 °C. Relative humidity: $\pm 10\%$.

** Typically achieved after extended period of unperturbed continuous operation of over 12 months. Temperature variation ± 0.25 °C. Relative humidity: $\pm 10\%$.

Environmental

- Temperature sensitivity $<1.0 \times 10^{-14}/^{\circ}\text{C}$
- Magnetic sensitivity $<3.0 \times 10^{-14}/\text{Gauss}$
- Power source sensitivity $<1.0 \times 10^{-14}$

Control

- Synthesized frequency resolution 7.0×10^{-17}
- Frequency control range 7.0×10^{-10}

Note: The synthesizer maintains continuous phase throughout frequency changes.

Available Outputs

Frequency	Amplitude
5 MHz	13 dBm
10 MHz	13 dBm
100 MHz	13 dBm

- Load impedance 50 Ω

Timing Output

- Format 1 PPS (positive going pulse)
- Amplitude >3 V into 50 Ω (TTL compatible)
- Pulsewidth 20 μs
- Rise time <3 ns
- Jitter <10 ps RMS

Timing Input

- Auto-sync input 1 PPS
- Amplitude >3 V into 50 Ω (TTL-compatible)
- Pulsewidth ≥ 20 μs
- Rise time <5 ns
- Jitter <1 ns RMS
- Synchronization input to output: <15 ns

Phase Noise $\mathcal{L}(f)$

Bandwidth	Outputs		
	5 MHz	10 MHz	100 MHz
1 Hz	≤ -116 dBc	≤ -110 dBc	≤ -90 dBc
10 Hz	≤ -135 dBc	≤ -129 dBc	≤ -109 dBc
100 Hz	≤ -148 dBc	≤ -142 dBc	≤ -122 dBc
1 kHz	≤ -155 dBc	≤ -149 dBc	≤ -129 dBc
10 kHz	≤ -155 dBc	≤ -149 dBc	≤ -129 dBc
100 kHz	≤ -155 dBc	≤ -149 dBc	≤ -129 dBc

Microsemi MHM 2010™

Active Hydrogen Maser

Low Phase Noise Option

Bandwidth	Outputs		
	5 MHz	10 MHz	100 MHz
1 Hz	≤-130 dBc	≤-124 dBc	≤-102 dBc
10 Hz	≤-150 dBc	≤-138 dBc	≤-117 dBc
100 Hz	≤-158 dBc	≤-146 dBc	≤-126 dBc
1 kHz	≤-160 dBc	≤-150 dBc	≤-133 dBc
10 kHz	≤-160 dBc	≤-153 dBc	≤-134 dBc
100 kHz	≤-160 dBc	≤-153 dBc	≤-134 dBc

Power

- Operating voltage 85 VAC to 264 VAC
- Frequency range 47 Hz to 63 Hz
- Peak power 150 W
- Operating power 75 W
- External DC input 22 VDC to 28 VDC
3.1 A (typical)
- Standby battery pack 8 hours of operation

Physical

- Height 42.0" (106.68 cm)
- Width 18.0" (45.72 cm)
- Depth 30.0" (76.0 cm)
- Weight 475 lbs (216 kg)
(without batteries***)

*** Add 66 lbs (30 kg) for batteries.

Ordering Information

Part Number	Description
75001-101	(3) 5 MHz, (1) 10 MHz, (1) 100 MHz
75001-102	(3) 5 MHz, (1) 10 MHz, (2) 100 MHz
75001-103	(3) 5 MHz, (1) 10 MHz, 1PPS sync, 1PPS output
75001-104	(3) 10 MHz, 1PPS sync, (2) 1PPS output
75001-105	(2) 5 MHz, (1) 100 MHz, 1PPS sync, 1PPS output
75001-106	(2) 5 MHz, (2) 10 MHz, 1PPS sync, (2) 1PPS output
75001-107	(2) 5 MHz, (2) 10 MHz, (1) 100 MHz
75001-108	(2) 5 MHz, (1) 10 MHz, (1) 100 MHz, 1PPS sync, 1PPS output
75001-109	(3) 5 MHz, (2) 10 MHz, (2) 100 MHz
75001-110	(3) 5 MHz, (3) 10 MHz
75001-111	(4) 5 MHz, (2) 10 MHz
75001-112	(3) 10 MHz, (2) 100 MHz, 1PPS sync, (2) 1PPS output
75001-113	(3) 5 MHz, (1) 10 MHz, (2) 100 MHz, 1PPS sync, 1PPS output
75001-114	(3) 5 MHz, (1) 10 MHz, (1) 100 MHz, 1PPS sync, (2) 1PPS output

Note: To order the optional Low Phase Noise option of the maser add LPN to the end of the part number. For example 75001-101 LPN.



Microsemi Corporate Headquarters

One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Fax: +1 (949) 215-4996
 Email: sales.support@microsemi.com
 www.microsemi.com

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.